



#### **ACTIVE CARBON FILTER CARTRIDGES**

For removal of chlorine, foul taste and odors, and organic matter

# ACTIVE CARBON FILTER CARTRIDGES

# ACF SERIES FILTERS FOR REMOVAL OF CHLORINE, FOUL TASTE AND ODORS, AND ORGANIC MATTER

ACF Series Filter Cartridges are made from active carbon fiber wrapped in non-woven polypropylene. The filters combine the performance of depth filtration and the adsorption of activated carbon fiber. The outside layer of polypropylene media can remove particles, and the activated carbon can remove chlorine, foul taste and odors, and organic matter effectively.

FEATURE	BENEFIT
Combined polypropylene outer media with inner activated carbon media	Multi-media construction provides high flow rates with good adsorption capability
	Wide chemical compatibility
	High resistance to acid and alkali liquids
	Strong absorption ability to remove chlorine, pigments, and odors
	No fiber release

## **SPECIFICATIONS**

Filter media	Active Carbon Fiber
Support/Core	Polypropylene
Max. Operating temperature	70°C
Max. Operating pressure	0.30 MPa (3.0 bar, 43.5 psi) at 21°C 0.12 MPa (1.2 bar, 17.4 psi) at 70°C
Nominal O.D.	64 mm (2.50")
Nominal I.D.	30 mm (1.18")
Mean Pore Size	5 µm




### **APPLICATIONS**

- · Water De-chlorination
- Electroplating bath
- · Drinking water and R.O. pure water treatment
- · Odor removal
- · Organic pigment removal

### **ABSORPTION OF CHLORINE**

Detectable Remaining Chlorine Level After 2 ppm Inlet @ 20 L/min



#### **ORDERING INFORMATION**

EXAMPLE: ACFR16TF10E-F 1600 mg/g, 222 o-ring connection, 10", with EPDM seals

**ACF** 



Adsorption of Iodine (mg/g)

**R8** = 800

**R10** = 1000

**R16** = 1600

**R18** = 1800

**End Cap** 

H = Double Open End (PE gasket)

TF = 222 O-ring/fin

SF = 226 O-ring/fin

TC = 222 O-ring/flat

SC = 226 O-ring/flat



**Nominal Length** 

**10** = 10" **20** = 20"

0 = 20

**30** = 30" **40** = 40"



**Seal Material** 

S = Silicone

E = EPDM

Blank = PE gasket,

(DOE option)

