

MultiPoly® FILTER CARTRIDGES

MULTI-LAYER PLEATED POLYPROPYLENE MEDIA FOR PRE-FILTRATION AND ELIMINATION OF CONTAMINANTS IN HIGHLY VISCOUS LIQUIDS, INCLUDING GELS AND AGGLOMERATES, COLLOIDS, AND SUSPENDED PARTICULATES

MultiPoly® Filter Cartridges are composed of multi-layered pleated polypropylene. These filters have a depth filter design that includes graded pore size and high contaminant holding capacity which eliminates contaminants (including gels and agglomerates) in highly viscous liquids, and avoids filter surface plugging. The graded pore size distribution from coarse (upstream) to fine (downstream) removes particles gradually and extends the filter's service life making it especially suited for suspended particulates, colloids, and viscous liquids.


FEATURE

BENEFIT

5 to 7 layers of PP media with graded pore size distribution

Enables additional particle loading and high contaminant holding capacity

Low pressure drop, long service life, filtration efficiency



Multi-layer nano fiber media

Provides excellent removal of contaminants including gels and agglomerates

Polypropylene construction

Excellent chemical compatibility

QUALITY STANDARDS

Quality Assurance

These products are manufactured in a facility which adheres to ISO 9001 Practices.

Particle Shedding

Autoclaved filter effluent meets the requirements in USP <788> for large volume injections

Non-Fiber Releasing

Component materials meet the criteria for a "Non-fiber-releasing filter" as defined in 21 CFR 210.3 (b) (6)



Typical Applications


- Gel Materials
- High Viscosity Materials
- Chemicals




SPECIFICATIONS

Filter media	Multi-Layer Nano Fiber Polypropylene
Supports/core/cage/end caps	Polypropylene
Effective filtration area	0.26 - 0.29m ² (2.7 - 3.1ft ²)/ 10" x Layers
O-rings	Silicone, EPDM, FKM, FEP/PFA encapsulated FKM
O-ring internal insert	PBT
Cartridge diameter	69 mm (2.7 in.)
Max. Operating pressure	0.69 MPa (6.9 bar, 100 psi) at 25°C 0.40 MPa (4.0 bar, 58 psi) at 60°C 0.24 MPa (2.4 bar, 35 psi) at 80°C
Max. Differential pressure	Forward: 0.69 MPa (6.9 bar, 100 psi) at 25°C 0.40 MPa (4.0 bar, 58 psi) at 60°C 0.24 MPa (2.4 bar, 35 psi) at 80°C Reverse: 0.3 MPa (3.0 bar, 44 psi) at 25°C 0.1 MPa (1.0 bar, 15 psi) at 80°C

FLOW RATES



MULTIPLE LAYERS OF MEDIA



ORDERING INFORMATION

EXAMPLE: **PFSA21000HSF10E-C** = 10 μm, 226/Fin, 10" filter with EPDM seals

PFSA2 **-C**

<p>Removal Rating</p> <p>0020 = 0.2 μm 1000 = 10 μm 0030 = 0.3 μm 2000 = 20 μm 0050 = 0.5 μm 4000 = 40 μm 0060 = 0.6 μm 5000 = 50 μm 0120 = 1.2 μm 7000 = 70 μm 0150 = 1.5 μm 9000 = 90 μm 0200 = 2.0 μm 15000 = 150 μm 0500 = 5.0 μm</p>	<p>Connection</p> <p>DOE = Double Open End, Flat Gasket HTC = 222 O-ring/Flat (PBT insert) HTF = 222 O-ring/Fin (PBT insert) HSC = 226 O-ring/Flat (PBT insert) HSF = 226 O-ring/Fin (PBT insert)</p>	<p>Nominal Length</p> <p>05 = 5" 10 = 10" 20 = 20" 30 = 30" 40 = 40"</p>	<p>Seal Material</p> <p>S = Silicone E = EPDM V = FKM P = E-FKM (FEP/PFA encapsulated FKM)</p>
---	--	---	---



BANNER INDUSTRIES IS THE EXCLUSIVE DISTRIBUTOR FOR COBETTER PRODUCTS IN THE USA
Visit www.bannerindustries.com and select the Contact Us link to find the location nearest you. The Banner Industries of N.E., Inc. Terms and Conditions of Sale apply and are fully and expressly incorporated herein by reference and constitute a part of any contract for the purchase of the products described herein.

www.bannerindustries.com | Technical Sales: filtration@bannerindustries.com

CBBPP1051 Rev. 05122021
Copyright © 2021 Banner Industries, Inc. All rights reserved.
MultiPoly® is a registered trademark of Cobetter Filtration Equipment Co., Ltd.