



## **PJ-PP FILTER CARTRIDGES**


All polypropylene filters for high flow applications

# PJ-PP FILTER CARTRIDGES

# ALL POLYPROPYLENE CARTRIDGES FOR HIGH FLOW RATE FINE FILTRATION

Cobetter® PJ-PP Filter Cartridges with a graded pore size distribution from upstream to downstream, captures particles gradually, which prolongs filter service life. For large capacity applications. Each 10" length has 75 ft² of filter media.

FEATURE	BENEFIT
All polypropylene, graded pore size construction	Excellent chemical compatibility
	Low pressure drop and high flow rates
	Long service life



#### **QUALITY STANDARDS**

Quality Assurance	These products are manufactured in a facility which adheres to ISO 9001:2015 Practices.
Particle Shedding	Autoclaved filter effluent meets the requirements in USP <788> for large volume injections.
Non-Fiber Releasing	Component materials meet the criteria for a "Non-fiber-releasing filter" as defined in 21 CFR 210.3 (b) (6)
Indirect Food Additive	All component materials meet the FDA Indirect Food Additive requirements cited in 21 CFR 177–182, and EU framework regulation [1935/2004/EC].



## **Typical Applications**

- Beer Fine Filtration
- Wine Pre-Filtration
- · Process Water
- Clarification
- RO Water Pre-Filtration
- Industrial Water Treatment

#### **SPECIFICATIONS**

Filter Media	Pleated Polypropylene Media
Cage/Support	Polypropylene
Core/End Caps	Polypropylene
Effective filtration area	75 ft <sup>2</sup> (7.0 m <sup>2</sup> ) / 10 inch
Diameter	270 mm (10.63 in.)
0-rings	Silicone, EPDM, FKM
O-ring Size	2-242, Ø4.05 in. (103 mm), Width: 0.14 in. (3.55 mm)
Max. Differential Pressure	Forward: 0.40 MPa (4.0 bar, 58 psi) at 21°C 0.10 MPa (1.0 bar, 14.5 psi) at 90°C Reverse: 0.15 MPa (1.5 bar, 22 psi) at 21°C
Steam Sterilization	30 minutes at 121°C at Max. Differential Pressure of 0.5 bar (7.25 psi)
Hot Water Sterilization	30 minutes at 85°C at Max. Differential Pressure of 2.0 bar (29 psi)
Cleaning Solution	2% NaOH Solution @ ≤65°C

Filter housings are custom made for your specific application with the configuration and fittings that are needed for installation. Please contact us for more information.

#### **ORDERING INFORMATION**

EXAMPLE: PJ-PP004520S-F = PJ-PP Cartridge, PP pleated media, 0.45 µm, 20 inch, silicone seals, Food & Beverage application

