

GasPro™ TEM-1500

High-Flow All-Fluoropolymer-316L In-Line Filter

GasPro™ TEM-1500 Series filters are specifically designed for filtration of UHP semiconductor gases when flow rates to 991 lpm (35 scfm) are required. This all-welded assembly will deliver 0.003 micron particle retention where a high flow rate is required and space is limited. A variety of fitting types is offered for easy installation.

A PTFE Membrane and all-fluoropolymer support structure is enclosed in a 316L stainless steel electro-polished welded housing. Final assembly is purged with filtrated nitrogen for initial cleanliness.



Features and Benefits

- **3nm Filter Rating**
Our porous PTFE filters provide efficient particle retention efficiency at $\geq 0.003\mu\text{m}$
- **High Flow**
GasPro™ TEM -1500 is rated to 991 lpm (35 scfm)
- **PTFE Media / All fluoropolymer Support Structure**
0.19 m² (2 ft²) PTFE filter media provides excellent flow and chemical resistance.
- **Electro-polished 316L housing**
The filter assemblies have a 10Ra electro-polished 316L stainless steel housing to prevent corrosion and particle formation.
- **Temperature and Pressure**
Operating temperature rating of 150°C (302°F) and Operating pressure rating of 17.2 bar (250 psig)
- **Cleanroom manufactured**
Our GasPro™ TEM-1500 filters are manufactured in a cleanroom to insure particle free, chemically clean, and organic-free handling and bagging to provide high out-of-package cleanliness. Additional preconditioning is optional.
- **100% helium tested to greater than 1x10⁻⁹ atm cc/second.**

Viton is a registered trademark of The Chemours Company



Specifications


Part Numbers / Ordering Information

Part Number	Inlet/Outlet Fittings	Filter Media / Housing	Other Material*	Length(L) (in/mm)
TEM-1515-8	3/8" male face seal inlet/outlet	PTFE / 316L Stainless Steel	All Fluoropolymer / FEP encapsulated Viton	6.75/172
TEM-1515-8	1/2" male face seal inlet/outlet			7.75/197
TEM-1550-8	1/2" butt weld			7.75/197


* FEP encapsulated FKM O-rings are available upon request

* Not all fittings, lengths and part numbers are shown on the chart. Please contact your Porvair representative or an approved Porvair distributor for special length and fitting options.

Gas Flow Rate / Pressure Drop



Dimensions



porvair
filtration group

Porvair Filtration Group Inc.

1226 Caldwell Blvd.
Nampa, Idaho 83651
Tel: +1 208 461 2090
Fax: +1 208 461 5794

Porvair High-Purity Gas Product
Information
Info@GasProfilters.com

Porvair Filtration Group Ltd.

1 Concorde Close
Segensworth, Fareham
Hampshire, PO15 5RT, UK
Tel: +44 (0) 1489 864330
Fax: +44 (0) 1489 864399

www.porvairfiltration.com

Porvair is a registered trademark of Porvair plc.

GasPro is a trademark of Porvair plc.

Hasfelloy is a registered trademark of Haynes International Inc.

VCR is a registered trademark of Swagelok Company.

© Copyright 2017, Porvair Filtration Group Ltd. All rights reserved.

While every effort has been made to ensure the accuracy of this document, due to continuous product development, the data contained is subject to constant revision and Porvair Filtration Group Ltd. reserves the right to change, alter or modify its contents.