

GasPro™ TEM-1900

High Purity All
Fluoropolymer 316L
In-Line Filter



GasPro™ TEM-1900 series filters are specifically designed for the filtration of UHP semiconductor gases. This all-welded assembly will deliver 0.003 micron particle retention where a high flow rate is required and space is limited.

A PTFE membrane and all fluoropolymer support structure is enclosed in a 316L stainless steel electro-polished welded housing.

Final assembly is purged with filtrated nitrogen for initial cleanliness.

A variety of fitting types is offered for easy installation.

Applications

- Point-of-use filtration of process speciality gases.
- Low pressure to vacuum delivery of silicon precursors via vapor or inert carrier gas.


Specifications

- **3nm filter rating**
Our porous PTFE filters provide efficient particle retention efficiency at 0.003µm.
- **Maximum operating temperature**
121°C (250°F).
- **Maximum operating pressure**
207 bar (3000 psig) at 20°C (68°F).

Features and benefits

- **PTFE media / all fluoropolymer support structure**
PTFE filter media provides excellent flow and chemical resistance.
- **Electro-polished 316L housing**
The filter assemblies have a 10Ra electro-polished 316L stainless steel housing to prevent corrosion and particle formation.
- **Cleanroom manufactured**
Our GasPro™ TEM-1900 filters are manufactured in a cleanroom to ensure particle free, chemically clean, and organic-free handling and bagging to provide high out-of-package cleanliness. Additional preconditioning is optional.
- **100% Helium tested**
100% Helium tested to greater than 1x10⁻⁹ atm cc/second.

Gas flow rate / Pressure drop



TEM-1900 Part Numbers and Ordering Information

Part Number	Inlet/Outlet Fittings	Filter Media / Housing	Other Materials	Length (L)
TEM-1911	1/4" compression inlet/outlet	PTFE / 316L stainless steel	All fluoropolymer / FEP encapsulated Viton®	116.8mm (4.6")
TEM-1911-6	3/8" compression inlet/outlet			122.2mm (4.81")
TEM-1911-8	1/2" compression inlet/outlet			122.7mm (4.83")
TEM-1915	1/4" male face seal inlet/outlet			127mm (5.00")
TEM-1915-6	3/8" male face seal inlet/outlet			133.4mm (5.25")
TEM-1915-8	1/4" butt weld inlet/outlet			133.4mm (5.25")
TEM-1950-8	1/2" butt weld inlet/outlet			130.3mm (5.13")

Not all fittings, lengths, and part numbers are shown on the chart. Please contact your Porvair representative or an approved Porvair distributor for special length and fitting options.



Porvair Filtration Group Ltd.

Queensway
Stem Lane, New Milton,
Hampshire, BH25 5NN, UK
Tel: +44 (0)1425 612010
Email: microelectronics@porvairfiltration.com

Porvair Filtration Group Inc.

1226 Caldwell Blvd.
Nampa, Idaho 83651, USA
Tel: +1 208 461 2090
Fax: +1 208 461 5794
Email: microelectronics@porvairfiltration.com

Porvair Filtration Group

Chengdong Area
Square Industrial Park, North District
Xiaonan Economic Development Zone
Xiaogan, 432000, China
Tel: +86 (0)712 2878955
Email: infoCN@porvairfiltration.com

Porvair Filtration India PVT. Ltd.

Gangothri Glacier Annex, Kavesar
Opposite Vijay Nagari, Off Ghodbunder Road
Thane (W), 400607, India
Tel: +91 22 25 976464 / +91 22 25 976465
Email: infoIN@porvairfiltration.com

Porvair is a registered trademark of Porvair plc.

GasPro is a trademark of Porvair plc.

Teflon is a trademark of The Chemours Company FC, L.L.C.

Viton is a registered trademark of DuPont Performance Elastomers L.L.C.

© Copyright 2018, Porvair Filtration Group Ltd. All rights reserved.

Whilst every effort has been made to ensure the accuracy of this document, due to continuous product development, the data contained is subject to constant revision and Porvair Filtration Group Ltd. reserves the right to change, alter or modify its contents.